

Bidco External Joint Wrap

Designed to create a high performance seal in precast structures and pipe joints



External Joint Wrap is a custom compounded butyl-based sealant specifically designed to create a high performance seal in precast structures and pipe joints.

FEATURES

Excellent adhesive and cohesive strength

Self-priming and self-healing

Highly resistive to temperature extremes and acid or caustic environments

Remains permanently flexible

Easily applied, high-performance seal

External Joint Wrap is highly effective when used in installations where hydrostatic or vacuum testing is required.

External Joint Wrap – Sizing Chart

Part Number	Width & Length (inches)	Rolls Per Carton	Linear Feet Per Carton	Pallet Size # Cartons/lbs.
BW-6T	6" x 50'	4	200	45 ctns./34 lbs
BW-9T	9" x 50'	4	200	45 ctns./60 lbs
BW-10T	10" x 50'	4	200	45 ctns./55 lbs
BW-12T	12" x 50'	2	100	45 ctns./50 lbs

Bidco C56 Butyl Mastic Sealant – Sizing Chart

Width & Length (inches)	Cross Section	Rolls Per Carton	Linear Feet Per Carton	Pallet Size # Cartons/lbs.
.500" x 21.0'	oval	10	210	45 ctns./24 lbs
750" x 14.5'	.66 x .66	10	145	45 ctns./36 lbs
1.00" x 14.5'	.88 x .88	8	116	45 ctns./50 lbs
1.25" x 14.5'	.875 x 1.375	5	72.5	45 ctns./49 lbs
1.50" x 10.0'	1.125 x 1.5	5	50	45 ctns./47 lbs
1.50" x 14.5'	1.125 x 1.5	5	72.5	45 ctns./67 lbs
2.00" x 10.0'	1.5 x 2.0625	4	40	45 ctns./68 lbs



TRELLEBORG

WWW.TRELLEBORG.COM/PIPE-SEALS